

# Safety Data Sheet Argon/Helium/Carbon Dioxide Mix

Central McGowan 123 Roosevelt Road, St. Cloud, MN, 56301 800-569-1322

### Section 1: Product and Company Identification

Central McGowan 123 Roosevelt Road, St. Cloud, MN, 56301

Product Code: Argon/Helium/Carbon Dioxide Mix Synonyms: AHC E, AHC Q, AHC S, AHC T, AHC V Recommended Use: Usage Restrictions:

**Section 2: Hazards Identification** 



Hazard Classification: Hazard Statements: Precautionary Statements Storage: Gases Under Pressure Contains gas under pressure; may explode if heated

Protect from sunlight. Store in well-ventilated place.

### Section 3: Composition/Information on Ingredients

	CAS #	Concent	ration	
Argon	7440-37-1	90%		
Helium	7440-59-7	7.5%		
Carbon Dioxide	124-38-9	2.5%		
	Chemical Su	bstance	Chemical Family	Trade Names
Argon	ARGON, COMPRESSED		Inorganic gases	ARGON; UN 1006; AR
Helium	HELIUM		Inorganic gases	HELIUM GAS; HELIUM COMPRESSED; HELIUM-4; ATOMIC HELIUM; UN 1046; He
Carbon Dioxide	CARBON DIO GAS	DXIDE,	Inorganic gases	CARBONIC ACID GAS; CARBONIC ANHYDRIDE; CARBON DIOXIDE; CARBON OXIDE; UN 1013; CO2

# **Section 4: First Aid Measures**

	Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Argon	Not applicable route of exposure	Flush eyes with plenty of water.	Not applicable route of exposure	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
Helium	Wash exposed skin with soap and water.	Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
Carbon Dioxide	If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.	Contact with liquid: Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	Do not induce vomiting.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.

# Section 5: Fire Fighting Measures

Suitable Extinguishing Media		Products of Combustion	Protection of Firefighters		
Argon	Non-flammable gas	Not applicable	■ N/a ■ N/A		
Helium	Non-flammable. use suitable extinguishing media for surrounding fire.	Non-flammable	<ul><li>Non-flammable</li><li>non-flammable</li></ul>		
Carbon Dioxide	Non-flammable	Non-flammable	<ul> <li>Any appropriate escape-type, self-contained breathing apparatus.</li> <li>non-flammable</li> </ul>		

# Section 6: Accidental Release Measures

	Personal Precautions	Environmental Precautions	Methods for Containment
Argon	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.	None known.	Stop leak if possible without personal risk.
Helium	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.	Avoid soil, waterways, drains and sewers	Stop leak if possible without personal risk.
Carbon Dioxide	Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering. Do not touch spilled material.	Subject to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). Keep out of water supplies and sewers.	Stop leak if possible without personal risk.

	Methods for Cleanup	Other Information
Argon	Leaks may be detected by a soapy-water solution.	
Helium	Stop leak, evacuate area. Contact emergency personnel.	None
Carbon Dioxide	Stop leak, evacuate, remove source of ignition.	None

# Section 7: Handling and Storage

	Handling	Storage
Argon	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.	Avoid using in confined spaces.
Helium	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	Keep separated from incompatible substances.
Carbon Dioxide	Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.	Store and handle in accordance with all current regulations and standards

# Section 8: Exposure Controls/Personal Protection

	Exposure Guidelines
Argon	ARGON, COMPRESSED: ARGON: ACGIH (simple asphyxiant)
Helium	HELIUM: ACGIH (simple asphyxiant)
Carbon	CARBON DIOXIDE, GAS: CARBON DIOXIDE: 5000 ppm (9000 mg/m3) OSHA TWA 10000 ppm (18000 mg/m3) OSHA TWA
Dioxide	(vacated by 58 FR 35338, June 30, 1993) 30000 ppm (54000 mg/m3) OSHA STEL (vacated by 58 FR 35338, June 30, 1993) 5000
	ppm ACGIH TWA 30000 ppm ACGIH STEL 5000 ppm (9000 mg/m3) NIOSH recommended TWA 10 hour(s) 30000 ppm (54000
	mg/m3) NIOSH recommended STEL

#### **Engineering Controls**

Handle only in fully enclosed systems.

	Eye Protection	Skin Protection	<b>Respiratory Protection</b>
Argon	Eye protection not required, but recommended.	Protective clothing is not required. Wear appropriate chemical resistant gloves.	N/a
Helium	Eye protection not required, but recommended.	Protective clothing is not required. Protective gloves are not required.	Non-flammable
Carbon Dioxide	For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing. Wear insulated gloves.	Any appropriate escape- type, self-contained breathing apparatus.

#### **General Hygiene considerations**

Avoid breathing vapor or mist

- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

# Section 9: Physical and Chemical Properties

	Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor
Argon	Gas	Colorless	Colorless	N/A	Gas	Odorless
Helium	Gas	Colorless	Colorless	N/A	Gas	Odorless
Carbon Dioxide	Gas	Colorless	Colorless	N/A	Gas	Odorless
			·			
	Taste	Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits
Argon	Tasteless	Not flammable			Nonflammable	Nonflammable
Helium	Tasteless	Not flammable	Not available	Not available	Nonflammable	Nonflammable
Carbon Dioxide	Acid taste	Not flammable	Not available	N/A	Nonflammable	Nonflammable
	Lower Explosive Limits	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity
Argon	Nonflammable	-303 F (-186 C)	-308 F (-189 C)	500 mmHg @ -190 C	1.38 (Air=1)	Not applicable

	Lower Explosive Limits	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity
Helium	Nonflammable	-452 F (-269 C)	-458 F (-272 C) @ 26 atm	1719 mmHg @ - 268 C	0.138 (Air=1)	Not applicable
Carbon Dioxide	Nonflammable	Not available	-71 F (-57 C) @ 4000 mmHg	43700 mmHg @ 21 C	1.5 (Air=1)	1.522 @ 21 C

	Water Solubility	рН	Odor Threshold	Evaporation Rate	Viscosity	Molecular Weight
Argon	3.36% @ 20 C	Not applicable	Not available	Not applicable	0.0225 cP @ 25 C	39.948
Helium	0.94% @ 0 C	Not applicable	Not available	Not applicable	0.02012 cP @ 26.8 C	4.0026
Carbon Dioxide	Soluble	3.7 (saturated aqueous solution) @ 101.3 kPa (carbonic acid)	Not available	Not applicable	0.01657 cP @ 0 C	44.01

	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
Argon	AR	1.784 g/L @ 0 C	Not available	100%	Not applicable	Soluble : Organic solvents
Helium	He	0.1785 g/L @ 0 C	Not available	100%	Not applicable	Insoluble : Not available
Carbon Dioxide	C-O2	0.114	Not available	Not applicable	Not applicable	Soluble : Alcohol, acetone, hydrocarbons, organic solvents

# Section 10: Stability and Reactivity

	Stability	Conditions to Avoid	Incompatible Materials	
Argon	Stable at normal temperatures and pressure.	Protect from physical damage and heat. Containers may rupture or explode if exposed to heat.	No data available.	
Helium	Stable at normal temperatures and pressure.	Protect from physical damage and heat. Containers may rupture or explode if exposed to heat. Keep liquid helium from contact with air.	No data available.	
Carbon Dioxide	Stable at normal temperatures and pressure.	Protect from physical damage and heat. Containers may rupture or explode if exposed to heat. Avoid contact with water or moisture.	Combustible materials, oxidizing materials, metal salts, reducing agents, metal carbide, metals, bases	

Hazardous Decomposition Products		Possibility of Hazardous Reactions
Argon	No data available.	Will not polymerize.
Helium	Miscellaneous decomposition products	Will not polymerize.
Carbon Dioxide	Carbon monoxide	Will not polymerize.

# Section 11: Toxicology Information

#### Acute Effects

	Oral LD50	Dermal LD50	Inhalation
Argon	Not established	Not established	Nausea, vomiting, difficulty breathing, irregular heartbeat, headache, dizziness, disorientation, mood swings, tingling sensation, loss of coordination, suffocation, convulsions, unconsciousness, coma

	Oral LD50	Dermal LD50	Inhalation
Helium	Not available	Not available	Nausea, vomiting, difficulty breathing, irregular heartbeat, headache, fatigue, dizziness, disorientation, emotional disturbances, tingling sensation, loss of coordination, suffocation, convulsions, unconsciousness, coma
Carbon Dioxide	Not established	Not established	Ringing in the ears, nausea, irregular heartbeat, headache, drowsiness, dizziness, tingling sensation, visual disturbances, suffocation, convulsions, coma

	Eye Irritation	Skin Irritation	Sensitization
Argon	No information on significant adverse effects	No information on significant adverse effects	
Helium	Liquid: frostbite, blurred vision	Liquid: frostbite	Difficulty breathing
Carbon Dioxide	Irritation, frostbite, blurred vision	Liquid: blisters, frostbite	Difficulty breathing

#### **Chronic Effects**

	Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Argon	Not established	Not established	Not established	No data
Helium	Not available	Not available	Not available	No data
Carbon Dioxide	Not available	Not established	Available.	No data

### **Section 12: Ecological Information**

#### Fate and Transport

	Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Argon	Fish toxicity: Not available Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available
Helium	Fish toxicity: Not available Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available
Carbon Dioxide	Fish toxicity: 150000 ug/L 48 day(s) (Mortality) Brown trout (Salmo trutta) Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Relatively non-persistent in the environment. Moderately volatile from water.	Accumulates very little in the bodies of living organisms.	Leaches through the soil

# Section 13: Disposal Considerations

Argon	Dispose in accordance with all applicable regulations.
Helium	Dispose in accordance with all applicable regulations.
Carbon Dioxide	Dispose in accordance with all applicable regulations.

### U.S. DOT 49 CFR 172.101

#### **DOT Information For This Mixture**

Shipping Name Compressed gas, n.o.s.		
	(Argon, Helium, Carbon Dioxide)	
UN Number	UN1956	
Hazard Class	2.2	
Hazard Information	NonFlammable Gas	

#### Individual Component Information

	Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Argon	Argon, compressed	UN1006	2.2	Not applicable	2.2	75 kg or L	150 kg	N/A
Helium	Helium, compressed	UN1046	2.2	Not applicable	2.2	75 kg or L	150 kg	N/A
Carbon Dioxide	Carbon dioxide	UN1013	2.2	Not applicable	2.2	75 kg or L	150kg	None

### **Canadian Transportation of Dangerous Goods**

	Shipping Name	UN Number	Class	Packing Group / Risk Group
Argon	Argon, compressed	UN1006	2.2	Not applicable
Helium	Helium, compressed	UN1046	2.2	Not applicable
Carbon Dioxide	Carbon dioxide	UN1013	2.2	Not applicable

# Section 15: Regulatory Information

#### **U.S. Regulations**

	CERCLA Sections	SARA 355.30	SARA 355.40
Argon	Not regulated.	Not regulated.	Not regulated.
Helium	Not regulated.	Not regulated.	Not regulated.
Carbon Dioxide	Not regulated.	Not regulated.	Not regulated.

#### SARA 370.21

	Acute	Chronic	Fire	Reactive	Sudden Release
Argon	Yes	No	No	No	Yes
Helium	Yes	No	No	No	Yes
Carbon Dioxide	Yes	No	No	No	Yes

#### SARA 372.65

Argon	Not regulated.
Helium	Not regulated.
Carbon Dioxide	Not regulated.

#### **OSHA Process Safety**

ConA rocess ballety		
Argon	Not regulated.	
Helium	Not regulated.	
Carbon Dioxide	Not regulated.	

#### **State Regulations**

	CA Proposition 65
Argon	Not regulated.
Helium	Not regulated.
Carbon Dioxide	Not regulated.

**Canadian Regulations** 

	WHMIS Classification	
Argon	A	
Helium	A	
Carbon Dioxide	Α	

#### **National Inventory Status**

	US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)
Argon	Listed on inventory.	Not listed.	Listed on inventory.
Helium	Listed on inventory.	Not listed.	Not determined.
Carbon Dioxide	Listed on inventory.	Not listed.	Listed on inventory.

# Section 16: Other Information

	NFPA Rating
Argon	HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=SA
Helium	HEALTH=0 FIRE=0 REACTIVITY=0 SPECIAL=SA
Carbon Dioxide	HEALTH=3 FIRE=0 REACTIVITY=0 SPECIAL=SA
0 minimal bazard 1 alight bazard 2 madarata bazard 2 apyara bazard 1 aytroma bazard	

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard